LAUGFS GSE Innovative technology

LAUGFS 's new product - **4.00-9 PON (Press On Tire)** with wide ribbed tread pattern is a unique concept in GSE application, replacing conventional 4.00-8 /3.75 rib pattern for baggage carts - Ground Support Equipment in airports.

6-00





LAUGPS

6-00.4



The product is unique and innovative with wider ribs and deeper grooves, molded on a robust steel ring and mounted on a durable wheel, suitable for the relevant application. Wider & deeper tread pattern gives multifold life than the conventional tire. The steel band offers longer durability and improved load-carrying capacity, even under rough grounds. The rim, steel band & rubber act as a single consolidated wheel, ideally suitable for GSE, offering excellent durable life and very high load-bearing capability.

| Tire size | | Tread Pattern Smooth(SM)/ Traction(TR)/ Rib(R) | Tire Dimensions (inch) | | Tire Dimensions (mm) | | Finished tire weight | Finished Assembly weight | Pcs/20ft | Pcs/20ft (Assembly) |
|-----------|----|--|---------------------------|------------|-------------------------|------------|-------------------------|--------------------------------|----------|------------------------|
| inch | mm | | Max Width | O.D -/+ 2% | Max Width | O.D -/+ 2% | (Kg) | (Kg) | | |
| 4.00-9 | | RIB | 4.1 | 15.9 | 103.0 | 403.0 | 12.4 | 19.95 | 1450 | 900 |

| Other Parameters | Value (mm) |
|------------------|------------|
| TREAD WIDTH (TW) | 94.5 |
| SECTION HEIGHT | 87.6 |
| CROWN RADIUS | 150.0 |
| INSIDE DIAMETER | 227.7 |

Tire Load Capacities

| Counter balar | ced lift Trucks Load Capacity (kg) | Other Vehicles (Trailers) | | | | |
|------------------------------|------------------------------------|---------------------------|---------------|---------------|--|--|
| Load wheels Up to 16 km/h | Steering wheels Up to 25 km/h | Up to 6 km/h | Up to 10 km/h | Up to 25 km/h | | |
| 950 | 730 | 950 | 860 | 730 | | |

