LAUGFS CONFORT RANGE OF TIRES FOR FORKLIFT APPLICATIONS



Introducing **FORKLIFT TYRES IN XT+ TREAD PATTERN**, with aperture holes on sidewall and specially designed to provide extra comfort, and cushion offering comfortable ride even on uneven surfaces .











This solid tire comes with

- A unique aperture design that provides excellent comfort to the driver and better shock absorption to fragile or impact-sensitive loads.
- Energy efficient cushion middle layer that provides low heat buildup characteristics, reducing shock transfer on to the equipment.
- Wear resistant tread providing extended service life, stability and improved braking properties.

The tire has the distinct advantages as compared to normal forklift tires

- Longer and extended service life with improved wear property due to cooler runs.
- High shock absorption properties improving ride characteristics, equipment safety and reliability.
- Low energy consumption and lower cost of operation.
- Good stability and braking in high load applications with additional ride safety.

Tire Dimensions												
Tire size	Rim Size	Easy Fit (E.F)/ Normal(N)	Tread Pattern Smooth(SM)/ Traction(TR)/Rib(R) /Skid Steer(SKS)	Tire Dimensions (inch)		Tire Dimensions (mm)		Finished tire weight (Kg)	Pcs/20ft			
				Max Width	O.D -/+ 2%	Max Width	O.D -/+ 2%					
6.00-9	4.00E-09	EF/N	TR	5.3	20.7	135.4	524.7	25.4	640			
6.50-10	5.00F-10	EF/N	TR	6.3	22.6	160.0	573.0	34.6	480			
7.00-12	5.00S-12	EF/N	TR	6.6	25.7	168.6	653.4	47.2	320			
8.25-15	6.50-15	EF/N	TR	8.3	32.3	210.0	821.0	91.2	154			
28X9-15	7.00-15	EF/N	TR	8.43	27.05	214.0	687.0	50.4	264			
10.00-20	7.00-20	EF/N	TR	9.9	41.1	251	1045	170.8	90			

	Load capacity (Kg)									
Tire size	Fork Lift T	rucks	Other Vehicles (Trailers)							
	Load Wheels up to 25 Km/h	Load Steering Wheels up to 25Km/h	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h					
6.00-9	1603	1233	1603	1454	1233					
6.50-10	2035	1565	2035	1848	1565					
7.00-12	2539	1948	2539	2300	1948					
8.25-15	4130	3174	4130	3739	3174					
28X9-15	3278	2522	3278	2974	2522					
10.00-20	5217	4348	5217	4739	4348					

